

PRODUCT INFORMATION

DLG[®] ENDURANCE



Don & Low
MEMBER OF THRACE GROUP

PRODUCT SHAPE	PROPELLOR*
PRODUCT TYPE	Monofilament
POLYMER	Polyethylene
DTEX	12.000/6
COLOUR	Turf Green & Bright Green
FILAMENT WIDTH	1.2 MM
FILAMENT THICKNESS	380 MICRON
TWIST	30 Z
TENSILE STRENGTH	100 N
SHRINKAGE (AT 90°C)	7%

PERFORMANCE RESULTS:

DURABILITY	NO VISIBLE DAMAGE AFTER LISPORT XL TO FIFA QUALITY (6,010 LISPORT CYCLES)
BALL ROLL	PASSING FIFA QUALITY PRO REQUIREMENTS
SKIN FRICTION & ABRASION	PASSING FIFA QUALITY PRO REQUIREMENTS
UV CERTIFICATION	UVA

IMPORTANT NOTE:

DUE TO SHRINKAGE OF THIS PRODUCT, ENSURE THAT THE FINISHING TEMPERATURES DO NOT EXCEED 90°C. THE APPEARANCE OF THE FINAL TURF MAY CHANGE WHEN IT REACHES TEMPERATURES BEYOND 90°C.

*MORE PRODUCT INFORMATION IS AVAILABLE ON REQUEST

www.donlow.co.uk
dlg.donlow.co.uk



APPLICATIONS:

FOOTBALL
RUGBY
GAA
AUSTRALIAN RULES
FIVE-A-SIDE

